


Product information VITOKORK Soft

The product consists of agglomerated cork, coated on one side with a self-adherent PVC-foam.

Product composition



Application

VITOKORK Soft is used as distance and shipping pads on glass.

Product benefit

- easy to remove
- high compression resistance
- shock-absorbent
- slip-resistant

Technical data and product properties

density cork (DIN EN ISO 845)	ca. 190 kg/m ³	
compression resistance (DIN EN ISO 3386)	10 %	30 N/cm ²
	20 %	50 N/cm ²
	30 %	70 N/cm ²
	40 %	90 N/cm ²
	50 %	110 N/cm ²
temperature resistance	-30 °C to 60 °C	

VITOKORK Soft

Delivery forms

doubled and in bulk

aligned on roll without liner protection

aligned on roll with liner protection

for LISEC automatic processing, on roll or bobbin

for BYSTRONIC/LENHARDT automatic processing, on roll or bobbin

Processing

The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes. In a few cases the PVC foam leaves marks on glass, which are normally easy to remove with an appropriate cleaning agent.

Storage and shelf life

6 month after receipt of goods, when stored at 18 °C and 60 % relative humidity protected from sunlight, in original packaging.

Special Information

The data and technical information presented are characteristic or average data. All advices are given to the best of our knowledge. You are kindly requested to conduct your own tests to determine the suitability of our product for your application. Our General Conditions answer any questions on guarantees and liabilities for these products unless other legal regulations apply.

If you need further information about product safety, conformance, REACH or RoHS please send your e-mail to info@vito-irmen.de

version: 10/2016 jk